

7. (unchanged) The method of claim 6 in which the target location in its changed position lies on the rendered Bezier shape.

8. (amended) The method of claim 1, 23, or 24 in which the predefined [intended behavior is] behaviors are expressed in response functions that define the relationship between changes in positions of target locations and changes in positions of canonical locations.

9. (amended) The method of claim 3 in which the Bezier shape comprises a curve, the $d+1$ canonical locations define d sections in order along the shape from one end to the other end, and the predefined intended behavior comprises the following:

when the target location is in the first section, the one end is relocated, and the other end is constrained to its original location, and

when the target location is in the d th section, the other end is relocated and the one end is constrained to its original location.

10. (amended) The method of claim 1, 23, or 24 in which the Bezier shape comprises a d -degree curve, the one end and the other end comprise end points of the curve, and the target location comprises a point along the curve.

11. (amended) The method of claim 1, 23, or 24 in which the Bezier shape comprises a 3-degree curve and there are four canonical locations.

12. (amended) The method of claim 1, 23, or 24 in which the Bezier shape comprises a 2-degree curve and there are three canonical locations.

13. (amended) The method of claim 1, 23, or 24 in which the control points are adjusted using a pre-computed basis coefficient matrix.

14. (amended) The method of claim 1, 23, or 24 in which the Bezier shape comprises a surface and in which the position of the target location is determined by forming a mesh on the surface and searching quadrilaterals of the mesh.

15. (unchanged) The method of claim 11 further comprising processing the relocation information as a series of curve relocations.

16. (amended) A medium storing machine readable instructions arranged to cause a machine to

As-Sub
B2

receive relocation information indicative of a user-specified change in position of any arbitrary target location on a Bezier shape, the Bezier shape being governed by control points, and

in response to the relocation information, determine new positions for canonical locations on the shape based on predefined behaviors of the canonical locations.

17. (amended) A method comprising

receiving relocation information indicative of a user-specified change in position of any arbitrary target location on a Bezier shape, the Bezier shape being governed by control points,

in response to the relocation information, determining new positions for canonical locations on the shape based on predefined behaviors of the canonical locations, the predefined intended behaviors being expressed in scaled response functions that define the relationship between changes in positions of target locations and changes in positions of canonical locations,

adjusting the control points so that the Bezier shape contains the canonical locations in their new positions, and

rendering the Bezier shape based on the new positions of the canonical locations so that the target location in its changed position lies on the rendered Bezier shape.

18. (amended) A method comprising

enabling a user to drag a user interface element displayed on a Bezier shape to indicate a predefined distortion of the Bezier shape, the Bezier shape being governed by control points, the user interface element being displayed other than on a boundary of the shape, and

in response to the dragging, effecting the predefined distortion by setting new positions for the control points.

19. (unchanged) The method of claim 18 in which the intended predefined distortion is effected by modifying a surface equation to effect the setting of new positions of the control points.

20. (unchanged) The method of claim 18 in which the distortion is symmetric.

21. (unchanged) The method of claim 18 in which the distortion is wave-like.

22. (unchanged) The method of claim 18 in which the user interface element comprises a handle that is constrained to move in a single direction during dragging.

Add the following new claims.

A5
cont.

Sub BB
Ave
--23. A method comprising
receiving relocation information indicative of a user-specified change in position of a
target location on a Bezier curve or surface, the target location not being on a boundary of the
curve or surface, the Bezier curve or surface being governed by control points, and
in response to the relocation information, determining new positions for canonical
locations on the curve or surface based on predefined behaviors of the canonical locations.

Seed BB
24. A method comprising
enabling a user to drag a target location on a Bezier curve or surface to indicate a new
position for the target location, the target location not being on a boundary of the Bezier surface,
the Bezier curve or surface being governed by control points, and
in response to the dragging, determining new positions for canonical locations on the
curve or surface based on predefined behaviors of the canonical locations.--